

Light intensity measuring instrument

**testo 545 - Lux meter with
measurement site management**

Selection of up to 99 measurement sites

Logger function

Point or timed mean value calculation

Quick documentation on site with Testo fast printer



In order for light to be good light, the light intensity at workplaces, in hospitals, offices or schools must meet certain minimum values.

testo 545 is ideally suitable for testing and monitoring light intensity. Using the software available as an option, the user can create different measurement sites, and connect individually stored light intensity values to a curve. This "light profile" provides information on the regularity of the lighting.

With the integrated logger function, up to 3000 measurement values can be stored in the instrument. This allows the user to monitor the light intensity even over a longer period. The measurement results can be printed out directly on site with the Testo fast printer.

Technical data / Accessories

testo 545

testo 545 light meter incl. probe, batteries and calibration protocol

Part no. 0560 0545



Sensor type **Silicone photodiode**

Meas. range	0 to +100000 Lux
Accuracy ±1 digit	Accuracy to DIN 13032-1: f1 = 6% = V (Lambda) adaptation f2 = 5% = cos like rating
Resolution	1 Lux (0 to +32000 Lux) 10 Lux (0 to +100000 Lux)

General technical data

Display	LCD, 4 lines
PC	RS232 interface
Connection	Fixed cable, coiled
Memory	3000
Oper. temp.	0 to +50 °C
Storage temp.	-20 to +70 °C
Battery type	9V block battery
Battery life	50 h
Dimensions	220 x 68 x 50 mm
Weight	500 g
Housing material	ABS
Warranty	2 years

Accessories

Part no.

Accessories for measuring instrument

Transport case (plastic) for measuring instrument, probes and accessories for safe and orderly storage	0516 0445	
testo 312 Case for secure storage of measuring instrument for secure storage of measuring instrument	0516 0191	
Testo fast printer IRDA with wireless infrared interface; 1 roll thermal paper; 4 AA batteries	0554 0549	
External fast charger for 1-4 AA rech. batteries, incl. 4 Ni-MH rech. batteries with individual cell charging and charge control display, incl. impulse trickle charging, integrated discharge function, with built-in international mains plug, 100-240 V, 300 mA, 50/60 Hz	0554 0610	
Spare thermal paper for printer (6 rolls), permanent ink measurement data documentation legible for up to 10 years	0554 0568	
ComSoft Professional, Pro software incl. data archiving	0554 1704	
RS232 cable connects instrument to PC (1.8 m) for data transfer	0409 0178	
ISO calibration certificate/light; Calibration points 0;500;1000;2000;4000 Lux	0520 0010	